

# Secure Solid State Drives (SSD) Mercury TRRUST-Stor® MissionPak

MMRxxxAM6S-000lxx-01 (SATA SLC mode)

- Engineered to FIPS 140-2 and Common Criteria (CC) requirements (planned)
- SATA interface using rugged 7-pin connector
- Supports all popular military sanitization protocols plus self-destruct
- AES-256 XTS encryption with user-fillable keys
- Heavily ruggedized, water-resistant form factor

The Mercury TRRUST-Stor MissionPak SSD expands the concept of handheld storage by integrating the latest-generation Armor® 3D NAND processor with AES-256 XTS encryption, multiple key management modes and self-destruct capability into a heavily ruggedized, water-resistant form factor designed for ease of use in harsh, possibly insecure environments. The MissionPak SSD uses TLC NAND in SLC mode and includes the security and certifications of the popular ASURRE-Stor® SSD. It is the perfect choice for mission-critical applications where reliability, security and ruggedization are the keys to mission success.

#### Features

www.mrcy.com

- Single 3.3 to 5.5 V ± 5% supply
- Designed and manufactured in a secure DMEA-accredited facility
- Mercury proprietary Armor 4 NAND processor
- Third-generation 3D NAND flash technology.
  - TLC NAND running in SLC mode
- Host-usable capacity<sup>1</sup>
  - 165, 330 GB in SLC mode
  - Program erase cycles: 40,000 in SLC mode
- Total bytes written (TBW)

• 2.56 PB minimum (256 GB model) TBW =  $\left(\frac{\text{Capacity x PE}}{4}\right)$  PE = Program Erase

- FIPS 140-2 certified<sup>2</sup>
  - Compliant to the NIAP EE and AA protection profiles
  - User and Crypto Officer Roles

- Multiple key management modes including user TRRUST-Boot secure boot image
- AES key-flipper technology eliminates key burn-in
- Fast clear: less than 10 seconds
- Sequential read/write performance<sup>3</sup>: SATA: Up to 250 MB/s
- Ultra-strong LDPC hard/soft error correction
- UBER (uncorrectable bit-error rate): 10<sup>-18</sup>
- Ruggedized water-resistant potted enclosure (non-potted optional)
- Hot-swap capable

• MTBF: 2 million hours @ 25 °C, Telcordia

#### Mechanical

- Vibration: 40.0 Grms, 15-2000 Hz, 3 axes, 6 hrs
- Operating Shock: 3000 G, 0.5 ms, ½ sine 100 G, 11 ms, ½ sine
- Operating Temperature: -40 °C to +85 °C<sup>4</sup>
  - Boot holdoff from -55 °C to -40 °C
- Storage Temperature: -55 °C to +105 °C
- Humidity: 100% condensing; water immersion to 2 feet for 10 minutes.
- Altitude: 80,000 feet
- Weight: 80 grams (short from factor)

#### NOTES:

- 1. One Gigabyte (GB) = 1,000,000,000 bytes.
- 100 MB/s = 100,000,000 bytes per second.
- 2. Planned
- 3. Performance values based on 128 KiB sequential transfers, largest capacity model, and empty drive.
- 4. Data retention may diminish with extended storage or operation at temperatures above 70 °C. Operation at 85 °C requires maintaining Tcase at 85 °C or less.

# Typical Applications

DATASHEET



#### Product Dimensions (in millimeters)





The host side "plug" connector is available from <u>Spacecraft Connectors</u> <u>Corp. KwikSnap Series</u> (SCTAC).



Drawing not to scale

Pinout on 7-pin receptacle TX pin names are outputs from MissionPak RX pin names are inputs to MissionPak



24.26

MissionPak

Pin	Descri	ptions

Pin #	Description
1	+RX
2	5.0 V
3	-TX
4	+TX
5	Present_N
6	-RX
7	GND

### Part Numbering (dashes in the part number are required)

	<u>X XX xxx X M x m - 123 l xx - aa</u>
Product Series	
M = TRRUST-Stor® series, standard model without FIPS 140-2 or Common Criteria certifications	
A <sup>1</sup> = ASURRE-Stor <sup>®</sup> certified series with FIPS 140-2 and Common Criteria certifications.	
Form Factor	
MR = MissionPak (SATAI)	
NAND (capacity available to host) 128 = 165 GB host capacity 256 = 330 GB host capacity	
Encryption Type A = AES-256 XTS	
Media M = Standard Product	
Media Type 6 = 3-bit TLC 3D NAND	
Operating Mode S = SLC mode	
-	
Customizable Features Fields One, Two and Three G00 = Standard product, gray	
Operating Temperature I = Industrial ( -40 °C to +85 °C )	
Classification ES = Engineering sample F = FIPS-140-2 certified <sup>1</sup> 00 = Standard product	
-	

## Attributes –

- 01 Construction:	Lead free (R)
Interface Structure:	1 Lane (1)
Interface Type:	SATA 6 Gb/s (SA)
- 04 <sup>1</sup>	Construction: Leaded BGAs (L)
Interface Structure:	1 Lane (1)
Interface Type:	SATA 6 Gb/s (SA)
NOTE: 1. Planned	

#### Available Part Numbers

Engineering Samples	Production Products
MMR128AM6S-G00IES-01	MMR128AM6S-G00100-01
MMR256AM6S-G00IES-01	MMR256AM6S-G00100-01
AMR128AM6S-G00IES-04	AMR128AM6S-G00IF-04
AMR256AM6S-G00IES-04	AMR256AM6S-G00IF-04

#### Need More Help? Need a Variant of This Product?

Contact Mercury's Secure SSD application engineering team at secure.ssd@mrcy.com





Download our Demystifying Hardware Full Disk Encryption Technology for Military Data Storage

	$\neg$
( f	WP
<u>_</u>	<u> </u>

Download our Safeguarding Mission Critical Data Whitepaper



Download our Microelectronics Quick Reference Guide

The Mercury Systems logo, Innovation That Matters, TRRUST-Stor, ASURRE-Stor and Armor are registered trademarks and BuiltSECURE is a trademark of Mercury Systems, Inc. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

Copyright © 2021 Mercury Systems, Inc.



CORPORATE HEADQUARTERS 50 Minuteman Road Andover, MA 01810-1008 USA +1 (978) 967-1401

Andover, MA 01810-1008 US +1 (978) 967-1401 +1 (866) 627-6951 Fax +1 (978) 256-3599 5077.04E 0321 ds SSD Mercury TRRUST-Stor MissionPak RMM

