

RESX07-1U22F

22" Deep, Front I/O Rugged Rack Server

Low-latency,
high-throughput
rugged rack server

- Dual Intel® 3rd generation Xeon® Scalable processors up to 36 cores
- Designed, tested and manufactured in the U.S.
- Configurable - up to 6 expansion slots that support 1 NVIDIA A100 GPU
- Memory - up to 20 DIMM slots



TECHNICAL SPECIFICATIONS

Dual Intel 3rd generation Xeon Scalable processors

3 UPI links up to 11.2 GT/s

20 DIMM slots, up to 2,560 GB DDR4-3200 MHz

Intel Trusted Execution Technology (TXT) with integrated TPM 2.0

Management and Operating System

Windows, Linux OS

Contact factory for OpenBMC

IPMI 2.0 management

Expansion and Modular Maintainability

Up to 6 expansions slots:

- Slot 1: PCIe gen 4.0 dual-width x16 FHFL, up to 12" w/ FIO
- Slot 2: PCIe gen 4.0 single-width x16 FHFL, up to 7.5" w/ no IO
- Slot 3: PCIe gen 4.0 single-width x16 FHFL, up to 7.5" w/ RIO
- Slot 4: PCIe gen 4.0 single-width x16 HHFL, up to 7.0" w/ FIO
- Slot 5: PCIe gen 4.0 single-width x8 HHFL, up to 7.5" w/ FIO
- Slot 6: OCP3.0 PCIe gen 4.0 x16 w/ FIO

Up to 2 NVMe M.2 slots

Power Supply Options

Non-redundant AC and DC power options:

- 1000 W 120 VAC
- 1300 W 240 VAC
- 1000 W 48 VDC
- 750 W 28 VDC

Environmental*

Operating

Temperature: 0°C to 50°C, configuration dependent

Humidity: 5% - 90%, up to 50°C, non-condensing

Shock: 3 axis, 35 g, 25 ms

Vibration: 4.7 Grms vertical, 4.5 Grms longitudinal, 5 Hz to 2000 Hz

Non-Operating

Temperature: -40°C to 70°C, configuration dependent

Humidity: 5% to 90%, up to 50°C, non-condensing

Additional Options

Shock pins

Slide rails

Cable accessories

Partnering with



Mechanical

Height: 1U or 1.75" (44.45 mm)

Width: 17.36" (440.9 mm)

Depth: 22" (558.8 mm) from front to back, 21" (533.4 mm) from ear to back

Weight (Typical)*: 27 lb


19" rackmountable

* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.



Front View

Product Naming Chart



Corporate Headquarters

50 Minuteman Road
Andover, MA 01810 USA
+1 978.967.1401 tel
+1 866.627.6951 tel
+1 978.256.3599 fax

International Office

Regus Center, 26 Avenue Jean Kuntzmann
Montbonnot 38330, France
+33 608.419949 tel

Learn more

Visit: mrcy.com/servers
Contact: servers@mrcy.com



The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, and BuiltSECURE. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

