mercury

Quartz 5503 30 VPX SOSA aligned high-speed synchronizer and distribution board

Synchronizes up to 32 channels across four Quartz[®] boards

- Synchronizes sampling and data acquisition for multichannel systems
- Synchronizes up to 32 channels across four Quartz boards
- Provides single sample accurate synchronization between multiple channels and multiple boards



The Quartz 5503 SOSA aligned high-speed synchronizer and distribution board synchronizes multiple Mercury Quartz family boards within a system. It enables synchronous sampling and timing for a wide range of multichannel high-speed data acquisition, DSP, radar, EW and software radio applications.

An on-board programmable clock generator creates the sample clock along with the required complimentary clocks. Up to four Quartz RFSoC boards can be synchronized using the 5503, with each receiving a common clock along with timing signals that can be used for synchronizing, triggering and gating functions.

INTELLIGENT PLATFORM MANAGEMENT CONTROLLER

The 5503 uses Crossfield Technology LLC's Intelligent Platform Management Controller (IPMC) to provide a fully compliant and flexible management solution for Field Replaceable Units (FRU) that support the VITA 46.11 standard required by HOST and SOSA architectures. The IPMC provides a standardized implementation of FRU management interfaces, control signals, and sensor monitoring. The IPMC provides the Chassis Manager and higher-level System Management Software (SMS) access to FRU information, FRU control signals, and sensor monitoring functions so that they can identify, activate/deactivate, reset, and monitor health of the card and take appropriate system control actions.

The IPMC also provides a low-level path for configuration management and FRU maintenance through both IPMI messages and a Maintenance Port (MP) serial interface. The maintenance port provides a terminal mode command-line interface and supports monitoring, data uploads, and FRU level troubleshooting.



5503 BLOCK DIAGRAM



Model 5503 Quartz

INPUT SIGNALS

Model 5503 provides three RF input signals via the VITA 67.3 D connector to accept signals from external sources: one for reference clock, one for sync, and one for gate/trigger signals. The 5503's internal programmable clock generator can create sample clock frequencies from 1 to >5 GHz. The sample clock can be locked to the board's internal 100 MHz reference or locked to an external reference received on the reference clock connector. Similarly, sync and gate/trigger can be generated on-board via software or received from external sources through the sync and gate/trigger connectors.

OUTPUT SIGNALS

Model 5503 can synchronize up to four Quartz products. A multisignal sync interface is provided to each board to be synchronized containing sample clocks, reference clocks, and gate/trigger and sync signals. Four sync interfaces are provided in the VPX expansion plane, Two on P1 and two on P2. Connections between the 5503 and Quartz boards are provided through custom VPX backplanes or through backplane cables.

SYSTEM CONFIGURATIONS



CONFIGURATION AND OPERATION

All board modes and operations are controlled by an on-board processor. Commands to this processor are sent via a 1 GigE control plane interface on P1.

SPECIFICATIONS

Reference Input

Connector Type: VITA 67.3D

Input Impedance: 50 ohms

Input Level: 0 dBm to +10 dBm, sine wave

Reference Clock Frequency: 10 MHz to 100 MHz

Gate/Trig & Ref Sync Inputs

Connector Type: VITA 67.3D

Input Level: LVTTL

Sync Outputs

Quantity: 4

Connector Type: two on VPX-P1 expansion plane, two on VPX-P2 expansion plane

Signal Level: CML

Signals: Sample Clock, SysRef , AXI4 Stream Clock, Sync, Gate/Trig

Programmable VCX0:

Frequency Ranges: 1 GHz to >5 GHz Tuning Resolution: 32 bits Unlocked Accuracy: ±20 ppm

Environmental

Operating Temp: 0° to 50° C Storage Temp: -20° to 90° C

Relative Humidity: 0 to 95%, non-condensing

Physical

Dimensions:

- Depth: 170.61 mm (6.717 in)
- Height: 100 mm (3.937 in)

Weight: 13.8 oz. (390 grams).

Typical Power Consumption: ~25 watts

OpenVPX Compatibility

The 5503 is compatible with the following module profile, as defined by the VITA 65 OpenVPX Specification:

SLT3-PAY-1F1U1S1S1U1U4F1J-14.6.13-n



ORDERING INFORMATION

| Model | Description |
|--------------|--|
| 5503 | 3U VPX SOSA aligned high-speed synchronizer and distribution board |
| Ontions | Description |
| options | Description |
| | |
| -050 | Support for Quartz products |
| -050 -763 | Support for Quartz products Conduction-cooled, Level 3 |

COMPATIBLE PRODUCTS

| Model | Description |
|-------|---|
| 5550 | 8-Channel A/D & D/A Zynq UltraScale+ RFSoC Gen 1 Processor - SOSA Aligned 3U VPX |
| 5553 | 8-Channel A/D & D/A Zynq UltraScale+ RFSoC Gen 3 Processor - SOSA Aligned 3U VPX |

LIFETIME SUPPORT FOR QUARTZ PRODUCTS

Mercury offers worldwide customers shorter development time, reliable, rugged solutions for a variety of environments, reduced costs, and mature software development tools. We offer free lifetime support from our engineering staff, which customers can depend on through phone and email, as well as software updates. Take advantage of our 40 years of experience in delivering high-performance radar, communications, SIGINT, EW, and data acquisition MIL-Aero solutions worldwide.

mercury

Corporate Headquarters

50 Minuteman Road Andover, MA 01810 USA +1 978.967.1401 tel +1 866.627.6951 tel +1 978.256.3599 fax

International Headquarters Mercury International

Avenue Eugène-Lance, 38 PO Box 584 CH-1212 Grand-Lancy 1 Geneva, Switzerland +41 22 884 5100 tel Learn more Visit: mrcy.com/go/MP5503 For technical details, contact: mrcy.com/go/CF5503



The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, Quartz and Navigator. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.



© 2022 Mercury Systems, Inc. 1-0-102622-DS-05503