

RES Trust XR5 1U *Built*SECURE™

20" Deep, 4 Drive, Rear I/O Rugged Rackmount Server

- **RoT enforced boot and configuration management**
- **Cyber-resilient BIOS, composable security features**
- **Dual Intel® Xeon® E5-2600 v4 processors up to 14 cores**
- **Field-proven, approved design**
- **Compliant with commercial and defense environmental resilience standards**
- **Designed, tested and manufactured in the U.S.**



Technical Specifications

Dual Intel® Xeon® E5-2600 v4 processors; SKU options:

E5-2618L v4 (10 core, 2.2G Hz, 75 W)

E5-2648L v4 (14 core, 1.8G Hz, 75 W)

2 QPI up to 8 GT/s

Up to 128 GB DDR4 up to 2400 MHz memory

Intel® Trusted Execution Technology (TXT) with integrated TPM 2.0

Management and Operating System

BIOS: Mercury-specialized and supported

Cyber-resilient baseboard management controller

Red Hat® Enterprise Linux® v7 support

Secure hypervisor and Linux options

*Built*SECURE™ Embedded Framework

Built-in composable security feature set options

Expansion and Modular Maintainability

Up to 2 PCIe 3.0 x16 cards, half-height half-length

3 fixed fans

Power Supply Options

Single 550 W AC power supply 90-264 VAC (47/63 Hz, 8-4 Amps)

Environmental*

Operating

Temperature**: 0°C to 50°C, configuration dependent per MIL-STD-810H, Methods 501.5 and 502.5

Altitude: 0 ft - 12,500 ft per MIL-STD-810H, Method 500.5, Procedure I

Humidity: 5% to 95% (non-condensing)

Shock: 3 axis, 20 g, 11 ms 1/2 sine pulse per MIL-STD-810H, Method 516.8, Procedure I

Vibration: Per MIL-STD-167-1A, Type 1

Non-Operating

Temperature: -40°C to 70°C

Humidity: 5% to 95% (non-condensing)

Altitude: 0 ft - 30,000 ft per MIL-STD-810H, Method 500.5, Procedure I

Random Vibration: 4.67 Grms vertical, 4.5 Grms longitudinal/lateral

5 Hz to 2000 Hz per MIL-STD-810H, Method 514.8, Procedure I

Composite profile of category 4 (Composite Wheeled Vehicle) and Category 7 (C-17)

Additional Options

Shock pins

Front door filter

Compatible slide rails and brackets/ shelf system

Cable accessories

Tamper-evidence features

Mechanical

Height: 1U or 1.75" (44.45 mm)

Width: 17" (433.3 mm)

Depth: 20" (508 mm)

Weight (Typical)*: 26.3 lb (11.9 kg)

19" rackmountable

* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.


** To reach temperatures above 40°C, additional measures may need to be implemented such as throttling or enhanced airflow.

Custom Expertise


For tailor-made systems with specific security and environmental requirements, email sales@mrchy.com

Input/Output Versatility

Front View



Rear View



Innovation That Matters, and Mercury Systems are trademarks of Mercury Systems, Inc. Other product and company names mentioned may be trademarks and/or registered trademarks of their respective holders. Mercury Systems, Inc. believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

Copyright © 2021 Mercury Systems, Inc.

6544.01E-0419-DS-RETRUSTXR51UVBS

mercury

INNOVATION THAT MATTERS*

CORPORATE HEADQUARTERS

50 Minuteman Road • Andover, MA 01810 USA
(978) 967-1401 • Fax (978) 967-3330

INTERNATIONAL HEADQUARTERS • MERCURY INTERNATIONAL

Avenue Eugène-Lance, 38 • PO Box 584
CH-1212 Grand-Lancy 1 • Geneva, Switzerland
+41 22 884 5100