

# **RESX07-1U22R**

22" Deep, Rear I/O Rugged Rack Server

Low-latency, high-throughput rugged rack server

- Dual Intel® 3rd generation Xeon®
  Scalable processors up to 32 cores
- Designed, tested and manufactured in the U.S.
- Configurable up to
  6 expansion slots that support
  1 full-size GPU
- NVMe storage up to 8 E1.L SSDs



#### **TECHNICAL SPECIFICATIONS**

Dual Intel 3rd generation Xeon Scalable processors

3 UPI links up to 11.2 GT/s

16 DIMM slots, up to 2,048 GB DDR4-3200 MHz

Intel Trusted Execution Technology (TXT) with integrated TPM 2.0

### Management and Operating System

Windows, Linux OS OpenBMC

IPMI 2.0 management

# Expansion and Modular Maintainability

Up to 6 expansions slots:

- Slot 1: PCle gen 4.0 dual-width x16 FHFL, up to 12" w/ RIO (not available on 1U22RB)
- Slot 2: PCle gen 4.0 dual-width x16 FHHL, up to 7.5" w/ no IO (only available on 1U22RA)
- Slot 3: PCle gen 4.0 dual-width x16 FHHL, up to 7.5" w/ FIO (not available on 1U22RC)
- Slot 4: PCle gen 4.0 single-width x16 HHHL, up to 7.0" w/ RIO
- Slot 5: PCle gen 4.0 single-width x8 HHHL, up to 7.5" w/ RIO

 Slot 6: OCP3.0 PCle gen 4.0 x16 w/ RIO

Up to 8 slim or 4 standard 2.5" SATA drives (U.2 option available) or 8 E1.L NVMe storage drives

Up to 2 M.2 slots

# Power Supply Options

Non-redundant AC power option:

• 1000 W 120 VAC

## Environmental\*

Rugged Level 1 Standards

(EXCEPTION: CE-102 not supported)

## **Additional Options**

Shock pins

Slide rails

#### Mechanical

Height: 1U or 1.75" (44.45 mm)

Width: 17.36" (440.9 mm)

Depth: 22" (558.8 mm) from front to back, 21" (533.4 mm) from ear to back

Weight (Typical)\*: 27 lb

19" rackmountable

\* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.

Partnering with










## **Product Naming Chart**



#### RESX07-1U22RA



Front View



**Rear View** 

## RESX07-1U22RB



Front View



**Rear View** 

# mercury

### **Corporate Headquarters**

50 Minuteman Road Andover, MA 01810 USA

- +1978.967.1401 tel
- +1866.627.6951 tel
- +1 978.256.3599 fax

## International Headquarters Mercury International

Avenue Eugène-Lance, 38 PO Box 584 CH-1212 Grand-Lancy 1 Geneva, Switzerland +41 22 884 51 00 tel Learn more

Visit: mrcy.com/servers

Contact: servers@mrcy.com









The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, and BuiltSECURE. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.





© 2021 Mercury Systems, Inc. 6592.01E-0721-DS-RESX07-1U22R

ER-21-1027