


# Jade 71141A

1-channel 6.4 GHz A/D, or 2-channel 3.2 GHz A/D,  
2-channel 6.4 GHz D/A  
XMC module with Kintex UltraScale FPGA

## Complete radar and software radio interface solution

- Radar and communication receiver and transmitter
- Electronic Warfare transponder
- Waveform signal generator
- Wideband data acquisition
- Remote monitoring
- Sensor interfaces



**The Jade® 71141A is a high-speed analog-to-digital and digital-to-analog converter with programmable DDCs (digital downconverters) and DUCs (digital upconverters).** It is suitable for connection to HF or IF ports of a communications or radar system. Its built-in data capture and generator features offer an ideal turnkey solution as well as a platform for developing and deploying custom FPGA-processing IP.


It includes a 6.4 GHz, 12-bit A/D converter, dual 6.4 GHz, 14-bit D/As and a large DDR4 memory. In addition to supporting PCI Express Gen. 3 as a native interface, the 71141A includes optional high-bandwidth connections to the Kintex UltraScale FPGA for custom digital I/O.

## FEATURES

- Xilinx® Kintex® UltraScale™ FPGA
- Supports VITA-49.2 VITA Radio Transport standard
- One-channel mode with 6.4 GHz, 12-bit A/D
- Two-channel mode with 3.2 GHz, 12-bit A/Ds
- Programmable DDCs (digital downconverters)
- Two 6.4 GHz, 14-bit D/As
- Programmable DUCs (digital upconverters)
- 5 GB of 2400 MHz DDR4 SDRAM
- $\mu$ Sync clock/sync bus for multimodule synchronization
- PCI Express interface (Gen. 1, 2 & 3) up to x8
- Optional LVDS and gigabit serial connections to the FPGA for custom I/O
- Ruggedized and conduction-cooled versions

## 71141A BLOCK DIAGRAM

Click on a block for more information.



## THE JADE ARCHITECTURE

Evolved from the proven designs of Mercury's Cobalt<sup>®</sup> and Onyx<sup>®</sup> families, Jade<sup>®</sup> raises the processing performance while lowering the overall power requirements by building on the Xilinx family of Kintex UltraScale FPGAs. As the central feature of the board architecture, the FPGA has access to all data and control paths, enabling factory-installed functions as well as providing an ideal platform for user-created intellectual property (IP).

Each member of the Jade family is delivered with factory-installed applications ideally matched to the board's analog interfaces. The 71141A factory-installed functions include two A/D acquisition and two D/A waveform generator IP modules. In addition, IP modules for DDR4 SDRAM memories, a controller for all data clocking and synchronization functions, a test signal generator and a PCIe interface complete the factory-installed functions and enable the 71141A to operate as a complete turnkey solution, without the need to develop any FPGA IP.

## EXTENDABLE IP DESIGN

For applications that require specialized functions, users can install their own custom IP for data processing. The Navigator<sup>®</sup> FPGA Design Kits include the board's entire FPGA design as a block diagram that can be edited in Xilinx's Vivado tool suite.

In addition to the block diagrams, all source code and complete IP core documentation is included. Developers can integrate their own IP along with the wide range of IP functions contained in the Navigator<sup>®</sup> IP library, or use the Navigator<sup>®</sup> kit to completely replace the IP with their own.

## XILINX KINTEX ULTRASCALE FPGAS

Depending on the requirements of the processing task, the Kintex Ultrascale can be selected from a range of FPGAs: KU035 through KU115. The KU115 features 5520 DSP48E2 slices and is ideal for modulation/demodulation, encoding/decoding, encryption/decryption, and channelization of the signals between transmission and reception. For applications not requiring large DSP resources or logic, a lower-cost FPGA can be installed.

## A/D AND DIGITAL DOWNCONVERTER STAGE

The board's analog interface accepts analog HF or IF inputs through a pair of front panel SSMC connectors with transformer-coupling into a Texas Instruments ADC12DJ3200 12-bit A/D. The converter operates in single-channel interleaved mode with a sampling rate of 6.4 GHz and an input bandwidth of 7.9 GHz; or, in dual-channel mode with a sampling rate of 3.2 GHz and input bandwidth of 8.1 GHz.

The A/D's built-in digital down-converters (DDCs) support 2x decimation in real output mode and 4x, 8x, or 16x decimation in complex output mode. The A/D digital outputs are delivered into the Kintex UltraScale FPGA for signal processing, data capture or for routing to other module resources.

## A/D ACQUISITION IP MODULES

The 71141A features two A/D Acquisition IP Modules for easy capture and data moving. The IP module can receive data from the A/D, or a test signal generator. The IP module has associated a 5 GB DDR4 memory for buffering data in FIFO mode or for storing data in transient capture mode.

In single-channel mode, all of 5 GB are used to store the single-channel of input data. In dual-channel mode, one half of the memory stores data from input channel 1 and the other half stores data from input channel 2. In both modes, continuous, full-rate transient capture of 12-bit data is supported.

The memory bank is supported with a DMA engine for moving A/D data through the PCIe interface. This powerful linked-list DMA engine is capable of a unique Acquisition Gate Driven mode. In this mode, the length of a transfer performed by a link definition need not be known prior to data acquisition; rather, it is governed by the length of the acquisition gate. This is extremely useful in applications where an external gate drives acquisition and the exact length of that gate is not known or is likely to vary.

For each transfer, the DMA engine can automatically construct metadata packets containing a sample-accurate time stamp and data length information. These actions simplify the host processor's job of identifying and executing on the data.

## VITA 49.2 RADIO TRANSPORT STANDARD

VITA 49.2 is a data transport protocol for conveying digitized signal information among signal acquisition/generation and processing elements in a communication, radar or similar system. The 71141A implements the VITA 49 packet format for the ADC/DDC data being transferred to the host memory via DMA.

VITA 49.2 packet elements always supported are:

- Signal Data Packet Type
- Stream Identifier
- Integer Seconds Timestamp
- Fractions Seconds Timestamp
- Trailer

Programmable elements are:

- Packet Size
- Stream Identifier
- Trailer

The Timestamp is automatically inserted from the metadata engine. After initialization an externally applied 1 PPS pulse will increment the Integer Seconds Timestamp. A division of the sample clock will increment the fractional seconds timestamp and this count is reset by the 1 PPS pulse.

VITA 49 packets sent via DMA to the DAC/DUC for output will have the header, stream ID, timestamp and trailer removed leaving only the signal data to be transmitted.

### D/A WAVEFORM GENERATOR IP MODULE

The 71141A factory-installed functions include a sophisticated D/A Waveform Generator IP module. It allows users to easily record to the dual D/A waveforms stored in either on-board memory or off-board host memory.

### DIGITAL UPCONVERTER AND D/A STAGE

A Texas Instruments DAC38RF82 DUC (digital upconverter) and D/A accepts a baseband real or complex data stream from the FPGA and provides that input to the upconvert, interpolate and dual D/A stages. When operating as a DUC, it interpolates and translates real or complex baseband input signals. It delivers real or quadrature (I+Q) analog outputs to the dual 14-bit D/A converter. Analog output is either through a pair of front panel SSMC connectors or the VITA 67.3C connector.

If translation is disabled, the DAC38RF82 acts as a dual interpolating 14-bit D/A. In both modes the DAC38RF82 provides interpolation factors from 1x to 24x.

### CLOCKING AND SYNCHRONIZATION

The 71141A accepts a half-rate sample clock via a front panel SSMC connector. In an alternate mode, the sample clock can be sourced from an on-board programmable frequency synthesizer. In this mode, the front panel SSMC connector can be used to provide a reference clock for synchronizing the internal oscillator. A third front panel SSMC connector accepts a TTL signal that can function as a Gate, Trigger Sync or PPS.

The Model 7192 high-speed sync module can be used to drive the sync bus to synchronize multichannel systems.

### MEMORY RESOURCES

The 71141A architecture supports a 5 GB bank of DDR4 SDRAM memory. User-installed IP along with the Mercury-supplied DDR4 controller core within the FPGA can take advantage of the memory for custom applications.

### PCI EXPRESS INTERFACE

The 71141A includes an industry standard interface fully compliant with PCI Express Gen. 1, 2, and 3 bus specifications. Supporting PCIe links up to x8, the interface includes multiple DMA controllers for efficient transfers to and from the module.

### XMC INTERFACE

The 71141A complies with the VITA 42.0 XMC specification. Each of the two XMC connectors provides an 8X link with up to 10 Gb/sec per lane. With dual XMC connectors, the 71141A supports x8 PCIe on the first XMC connector (P15), leaving the optional second connector (P16) free to support user-installed transfer protocols specific to the target application.

Option -104 installs the P14 PMC connector with 24 pairs of LVDS connections to the FPGA for custom I/O.

Option -105 installs P16 providing one 8X gigabit link between the FPGA and the P16 XMC connector to support serial protocols.


## NAVIGATOR DESIGN SUITE

For applications that require specialized functions, the Navigator Design Suite allows customers to fully utilize the processing power of the FPGA. It includes an FPGA design kit for integrating custom IP into the factory-shipped design, and a board support package for creating host applications for control of all hardware and FPGA IP-based functions.

The **Navigator FPGA Design Kit (FDK)** for the Xilinx® Vivado® Design Suite includes the complete Vivado project folder for each Jade product with all design files for the factory-installed FPGA IP. Vivado's IP Integrator is a graphical design entry tool that visually presents the complete block diagram of all IP blocks so the developer can access every component of the Jade design. Developers can quickly import, delete, and modify IP blocks and change interconnection paths using simple mouse operations.


Navigator FDK includes an IP core library of more than 100 functions representing a wealth of resources for DSP, data formatting, timing, and streaming operations, all based on the powerful AXI4 standard. multilevel documentation for each IP core is a mouse click away, and fully consistent with Xilinx IP cores.

The **Navigator Board Support Package (BSP)** provides software support for Jade boards. It enables operational control of all hardware functions on the board and IP functions in the FPGA. The BSP structure is designed to complement the functions of the FDK by maintaining a one-to-one relationship between FDK and BSP components. For each IP block found in the FDK library, a matching software module can be found in the BSP. This organization simplifies the creation and editing of software to support new IP functions and modifications to existing IP cores.




Navigator IP FPGA Design viewed in IP Integrator

## NAVIGATOR BOARD SUPPORT PACKAGE




## NAVIGATOR FPGA DESIGN KIT



Because all Jade boards are shipped with a full suite of built-in IP functions and numerous software examples, new applications can be developed by building on the provided software examples or built entirely new with the BSP extensive libraries. All BSP libraries are provided as C-language source for full access and code transparency.


The Navigator BSP includes the **Signal Viewer**, a full-featured analysis tool, that displays data in time and frequency domains. Built-in measurement functions display 2nd and 3rd harmonics, THD (total harmonic distortion), and SINAD (signal to noise and distortion). Interactive cursors allow users to mark data points and instantly calculate amplitude and frequency of displayed signals. With the Signal Viewer users can install the Jade board and Navigator BSP and start viewing analog signals immediately.





## FRONT PANEL CONNECTIONS

The front panel includes seven SSMC coaxial connectors for input/output of analog RF, clock, and trigger, signals, and a 12-pin Sync Bus input connector. The front panel also includes seven LED indicators.



- **ADC Overload LED:** There is one red **OV** (overload) LED for all ADC inputs. This LED indicates either an overload detection in one of the ADC12DJ3200s, or an ADC FIFO overrun.
- **Analog Input Connectors:** Two SSMC coaxial connectors, labeled **IN 1** and **IN 2**: one for each ADC input channel.
- **DAC Underrun LED:** One red **UR** LED for both DAC outputs. This LED illuminates when the DAC38RF82 FIFO is out of data.
- **Analog Output Connectors:** Two

SSMC coaxial connectors, labeled **OUT 1** and **OUT 2**: one for each DAC38RF82 output channel.

- **PPS LED:** The green **PPS** LED illuminates when a valid PPS signal is detected. The LED will blink at the rate of the PPS signal.
- **Trigger Input Connector:** One SSMC coaxial connector, labeled **TRIG**, for input of an external trigger.

- **Clock LED:** The green **CLK** LED illuminates when a valid sample clock signal is detected. If the LED is not illuminated, no clock has been detected and no data from the input stream can be processed.
- **Clock Input Connector:** One SSMC coaxial connector, labeled **CLK**, for input of an external sample clock.
- **Reference Clock Input Connector:** The SSMC coaxial connector, labeled **REF**, for input of an external reference clock.
- **Link LED:** The green **LNK** LED indicates the link speed when a valid link has been established over the PCIe interface, as follows: Gen 1 - LED blinks slowly (less than once per second); Gen 2 - LED blinks about once per second; Gen 3 - LED will be constantly on.
- **Sync Bus Connector:** The 19-pin  $\mu$ Sync front panel connector, labeled **SYNC/GATE**, provides sync and gate input signals for A/D and D/A Processing.
- **User LED:** The green **USR** LED is for user applications.
- **Over Temperature LED:** The red **TMP** LED illuminates when an over-temperature or over-voltage condition is indicated by any of the temperature/voltage sensors on the PCB.

## SPECIFICATIONS

### Analog Signal Inputs

Input Type: Two front panel SSMC connectors  
Full Scale Input: +1.0 dBm into 50 ohms  
Maximum Power Input: 12 dBm  
Input Impedance: 50 $\Omega$   
Coupling: Transformer coupled

Transformer Type:

Standard: Marki Microwave  
BALH-0006SMG

Option -201: Marki Microwave  
BALH-0003SMG

3dB Passband: 0.5 MHz to 6000 MHz (standard)

0.5 MHz to 3000 MHz (Option -201)

### Analog to Digital Converter

Type: Texas Instruments  
ADC12DJ3200 A/D converter

Sampling Rate, Resolution, Decimation: See [Configuration Modes table below](#).

Input Bandwidth:

- Single-channel mode: 7.9 GHz
- Dual-channel mode: 8.1 GHz

Output Interface: JESD204B to FPGA

Clock Source: Sample clock source can be selected from onboard frequency synthesizer or from External Sample Clock Input

### Analog Signal Outputs

Output Type: Two front panel SSMC connectors

Full Scale Output: +7.5 dBm into 50 ohms

Output Impedance: 50 $\Omega$

Coupling: Transformer coupled

Transformer Type: Mini-Circuits  
TCM3-452X-1+

3dB Passband: 20 MHz to 4000 MHz

### Digital to Analog Converters

Type: Texas Instruments DAC38RF82 D/A converter

Sampling Rate, Interpolation: See [Configuration Modes table below](#).

Resolution: 14 bits

Input Interface: JESD204B from FPGA

Clock Source: Sample clock source can be selected from onboard frequency synthesizer or from External Sample Clock Input

## Sync Bus Inputs/Outputs

Connector: Front panel 19-pin  $\mu$ Sync connector

Gate A In: 2 pins (CML pair)

Sync A In: 2 pins (CML pair)

Gate B In: 2 pins (CML pair)

Sync B In: 2 pins (CML pair)

TWSI Bus: 2 pins

## External Gate / Trigger / Sync / PPS Input

Connector Type: One front panel SSMC connector

Signal Type: LVTTTL

Functions: Programmable - trigger, gate, sync, PPS (see below)

## Internal Sample Clock Generator

Device: Texas Instruments LMX2594 Fractional-N frequency synthesizer

Reference Source: Selectable from external or internal reference

External Reference: (see External Reference Clock Input below)

One front panel SSMC connector (shared with External Sample Clock Input)

Internal Reference: Internal Programmable Frequency Reference

Synchronization: Frequency Synthesizer can be locked to an external 1 to 300 MHz PLL system reference, typically 10 MHz. An on-board internal reference source is also available (see below)

Maximum Synthesizer Output Frequency: 3255 MHz

## External Sample Clock Input

Connector: One front panel SSMC connector

Signal Type: AC signal, 50% duty cycle

Frequency Range: 10 MHz - 4 GHz input clock

Voltage Range: +0 to +10 dBm

Coupling: AC coupled

Input Impedance: 50 $\Omega$

## Effective Data Converter Sampling Frequency

Either 1x or 2x the internal sample clock generator or external clock, depending on data converter operating modes

## External Reference Clock Input

Connector: One front panel SSMC connector

Signal Type: AC signal, 50% duty cycle

Frequency Range: 0.6 to 300 MHz input clock

Voltage Range: -10 to +24 dBm

Coupling: AC coupled

Input Impedance: 50 $\Omega$

## Internal Programmable Frequency Reference

Device: Silicon Labs Si571 Any-Rate VCXO

Frequency Range: 10-945, 970-1134, 1213-1417.5 MHz

Start-Up Freq: 100 MHz

Freq Resolution: 0.09 ppb

## Gates

Quantity: Two separate gates: Gate A for A/D; Gate B for D/A

Gate Sources: Selectable from external or internal gate

External: (see External Gate / Trigger / Sync / PPS Input) or Sync Bus CML Gate

Internal: Generated from programmable register

Gate Polarity: Programmable polarity for external as well as internal gate

Triggering: Programmable trigger length

## Syncs

Quantity: Two separate syncs: Sync A for A/D; Sync B for D/A

Sync Source: Selectable from external or internal sync

External: (see External Gate / Trigger / Sync / PPS Input) or Sync Bus CML Sync

Internal: Generated from programmable register

Sync Pulse Width: 2 clock cycles, minimum

Sync Pulse Edge: Programmable selection of either rising edge or falling edge

## Field-Programmable Gate Arrays (FPGA)

- Standard: Xilinx Kintex UltraScale XCKU035-2
- Option -084: Xilinx Kintex UltraScale XCKU060-2
- Option -087: Xilinx Kintex UltraScale XCKU115-2 Configuration: IP Cores factory-programmed by Mercury

## Custom I/O

- Option -104: Installs the PMC P14 connector with 24 LVDS pairs to the FPGA
- Option -105: Installs the XMC P16 connector with one 8X gigabit serial link to the FPGA

## FPGA MGT Clock Generator

Device: Silicon Labs Si5341B Any-Rate Clock Generator

Type: 10 separate programmable clock outputs

Frequency Range: 100 Hz to 350 MHz

## RAM memory

Size: 5 Gigabytes of DDR4 SDRAM

Speed: 1200 MHz (2400 MHz DDR)

Bus Width: 80 bits

## Configuration FLASH memory

Size: 1 Gigabit

Bus Width: 16 bits

## Temperature and Voltage Sensors

PCB Temperature

Quantity: Four temperature sensors

Controller: Texas Instruments LM95234

PCB Power



Quantity: Four voltage inputs (two for 3.3V, two for 12V)

Controller: Linear Technology LTC2990

### PCB Voltage

Quantity: Five voltage sensors

Controller: Kintex UltraScale System Monitor

### PCI Express Interface

PCI Express: Gen. 1, 2 or 3: x4 or x8

Lanes/Speed: Gen1 x8 - 2 GB/sec

Gen2 x8 - 4 GB/sec

Gen3 x8 - 8 GB/sec

### Environmental

Standard: L0 (air-cooled)

- Operating Temp: 0° to 50° C
- Storage Temp: -20° to 90° C
- Relative Humidity: 0 to 95%, non-condensing

Option -702: L2 (air-cooled)

- Operating Temp: -20° to 65° C
- Storage Temp: -40° to 100° C
- Relative Humidity: 0 to 95%, non-condensing

Option -713: L3 (conduction-cooled)

- Operating Temp: -40° to 70° C
- Storage Temp: -50° to 100° C
- Relative Humidity: 0 to 95%, non-condensing

### Physical

Dimensions: Single PMC/XMC board

- Depth: 149.0 mm (5.87 in)
- Height: 74 mm (2.91 in)

Weight: Approximately 17 oz (480 grams)

### ORDERING INFORMATION

Model	Description
71141A	1-Ch. 6.4 GHz or 2-Ch. 3.2 GHz A/D, 2-Ch. 6.4 GHz D/A, Kintex UltraScale FPGA - VPX

#### Options:

-084	XCKU060-2 FPGA
-087	XCKU115-2 FPGA
-104	LVDS FPGA I/O through P14 connector
-105	Gigabit serial FPGA I/O through P16 connector
-109	VITA 66.5: Optical 4X duplex lanes
-201	5-3 GHz input transformer
-249	VITA 49-2 support
-702	Air-cooled, Level 2
-713	Conduction-cooled, Level 3

Contact Mercury for compatible option combinations and complete specifications of rugged and conduction-cooled versions. Options may change, so be sure to contact Mercury for the latest information.

### ACCESSORY PRODUCTS

Model	Description
2171	Cable kit: SSMC to SMA
7192	High-speed synchronizer and distribution board - PMC/XMC model
9192	Rackmount high-speed system synchronizer unit

## DEVELOPMENT SYSTEMS

Mercury offers development systems for Jade products. They come with all pre-tested software and hardware ready for immediate operation. These systems are intended to save engineers and system integrators the time and expense associated with building and testing a development system that ensures optimum performance of Jade boards. Please [contact Mercury](#) to configure a system that matches your requirements.

## FORM FACTORS

Jade products are available in standard form factors including 3U VPX, 6U VPX, PCIe, and XMC. The Jade Model 71141A XMC (8-Channel 250 MHz A/D with DDC, Kintex UltraScale FPGA) has the following variants:

Model	
52141A	3U VPX board (single XMC)
54141A	3U VPX board (single XMC with optical/backplane RF)
57141A	6U VPX board (single XMC)
58141A	6U VPX board (dual XMC)
71141A	XMC module
78141A	PCIe board (single XMC)

## LIFETIME SUPPORT FOR JADE PRODUCTS

Mercury offers worldwide customers shorter development time, reliable, rugged solutions for a variety of environments, reduced costs, and mature software development tools. We offer free lifetime support from our engineering staff, which customers can depend on through phone and email, as well as software updates. Take advantage of our 40 years of experience in delivering high-performance radar, communications, SIGINT, EW, and data acquisition MIL-Aero solutions worldwide.



### Corporate Headquarters

50 Minuteman Road  
Andover, MA 01810 USA  
**+1 978.967.1401** tel  
**+1 866.627.6951** tel  
**+1 978.256.3599** fax

### International Headquarters

**Mercury International**  
Avenue Eugène-Lance, 38  
PO Box 584  
CH-1212 Grand-Lancy 1  
Geneva, Switzerland  
**+41 22 884 5100** tel

### Learn more

Visit: [mrcy.com/go/MP71141A](https://mrcy.com/go/MP71141A)

For technical details, contact:  
[mrcy.com/go/CF71141A](https://mrcy.com/go/CF71141A)



The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, Jade and Navigator. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.



**71141A CONFIGURATION MODES**

Mercury's Model 71141A is capable of operating in the configurations listed below. Certain sampling rate ranges during independent as well as simultaneous A/D and D/A operation are not achievable due to the clocking limitations of the JESD204B interface. The Navigator BSP automatically selects the most appropriate ADC and DAC JESD modes based on the arguments supplied to the API routines. Parameters such as clock frequency, sample width and real/complex data are used while making the decision.

**ADC Standalone Operation**

Resolution	Real or Complex	Number of Channels	Sample Rate	Digital Downconverter
8-bit	real	2 CH	800 to 3200 MSPS	bypass
8-bit	real	1 CH	1600 to 6400 MSPS	bypass
16-bit	real	2 CH	800 to 3200 MSPS	bypass
16-bit	real	1 CH	1600 to 6400 MSPS	bypass
16-bit	complex	2 CH	800 to 3200 MSPS	decimate by 4
16-bit	complex	2 CH	800 to 3200 MSPS	decimate by 8
16-bit	complex	2 CH	800 to 3200 MSPS	decimate by 16

**DAC Standalone Operation**

Resolution	Real or Complex	Number of Channels	Sample Rate	Digital Upconverter
8-bit	real	1 CH	1600 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 1 interpolate by 1
16-bit	real	2 CH	400 to 2500 MSPS 2500 to 3200 MSPS*	interpolate by 1 interpolate by 1
16-bit	real	2 CH	800 to 3200 MSPS 5240 to 6400 MSPS*	interpolate by 2 interpolate by 2
16-bit	real	2 CH	1600 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 4 interpolate by 4
16-bit	complex	1 CH	400 to 2500 MSPS 2500 to 3200 MSPS*	interpolate by 1 interpolate by 1
16-bit	complex	1 CH	800 to 3200 MSPS 5240 to 6400 MSPS*	interpolate by 2 interpolate by 2
16-bit	complex	1 CH	1600 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 4 interpolate by 4
16-bit	complex	2 CH	1200 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 6 interpolate by 6
16-bit	complex	2 CH	1600 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 8 interpolate by 8
16-bit	complex	2 CH	2000 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 10 interpolate by 10
16-bit	complex	2 CH	2400 to 3200 MSPS 5240 to 6400 MSPS	interpolate by 12 interpolate by 12

Resolution	Real or Complex	Number of Channels	Sample Rate	Digital Upconverter
16-bit	complex	2 CH	3200 MSPS 5240 to 6400 MSPS	interpolate by 16 interpolate by 16
16-bit	complex	2 CH	5240 to 6400 MSPS	interpolate by 18
16-bit	complex	2 CH	5240 to 6400 MSPS	interpolate by 24

NOTE: \*Theses modes have an input resolution of 12 bits to achieve higher sample rates.

**Record/Playback Scenario, ADC and DAC Operating in Complementary Configurations  
(but not simultaneously)**

Resolution	Real or Complex	Number of Channels	Sample Rate	Digital Down/ Upconverter
8-bit	real	1 CH	1600 to 3200 MSPS 5240 to 6400 MSPS	bypass bypass
16-bit	real	2 CH	800 to 2500 MSPS 2500 to 3200 MSPS*	bypass bypass
16-bit	complex	1 CH	1600 to 3200 MSPS	dec/int by 4
16-bit	complex	2 CH	1600 to 3200 MSPS	dec/int by 8
16-bit	complex	2 CH	3200 MSPS*	dec/int by 16

NOTE: \*Theses modes have an input resolution of 12 bits to achieve higher sample rates.

**Full-Duplex Transceiver Scenario, ADC and DAC Operating Simultaneously  
in Complementary Configurations**

Resolution	Real or Complex	Number of Channels	Sample Rate	Digital Down/ Upconverter
8-bit	real	1 CH	5240 to 6400 MSPS	bypass
16-bit	real	2 CH	800 to 1000 MSPS 1600 to 2000 MSPS 2500 to 3200 MSPS	bypass bypass bypass
16-bit	complex	1 CH	1600 to 3200 MSPS	dec/int by 4
16-bit	complex	2 CH	1600 to 3200 MSPS	dec/int by 8
16-bit	complex	2 CH	3200 MSPS	dec/int by 16
16-bit	complex	2 CH	3200 MSPS* 6400 MSPS*	dec. by 8 int by 16

NOTE: \*Theses modes have an input resolution of 12 bits to achieve higher sample rates.