

# RESX07-2U22R

## 22" Deep, Rear I/O Rugged Rack Server

Low-latency,  
high-throughput  
rugged rack server

- Dual Intel® 3rd generation Xeon® Scalable processors up to 32 cores
- Designed, tested and manufactured in the U.S.
- Configurable - up to 6 expansion slots that support 4 NVIDIA A100 GPUs
- NVMe storage – up to 16 E1.L SSDs



### TECHNICAL SPECIFICATIONS

Dual Intel 3rd generation Xeon Scalable processors

3 UPI links up to 11.2 GT/s

20 DIMM slots, up to 2,560 GB DDR4-3200 MHz

Intel Trusted Execution Technology (TXT) with integrated TPM 2.0

#### Management and Operating System

Windows, Linux OS

Contact factory for OpenBMC

IPMI 2.0 management

#### Expansion and Modular Maintainability

Up to 6 expansions slots:

- Slot 1: PCIe gen 4.0 dual-width x16 FHFL, up to 12" w/ RIO
- Slot 2: PCIe gen 4.0 dual-width x16 FHFL, up to 12" w/ RIO
- Slot 3: PCIe gen 4.0 dual-width x16 FHFL, up to 12" w/ RIO
- Slot 4: PCIe gen 4.0 dual-width x16 FHFL, up to 12" w/ RIO
- Slot 5: PCIe gen 4.0 single-width x8 HHHL, up to 7.5" w/ RIO
- Slot 6: OCP3.0 PCIe gen 4.0 x16 w/ RIO

Up to 8, 2.5" SATA/SAS drives (U.2 option available) or 16 E1.L NVMe storage drives

Up to 2 M.2 slots

#### Power Supply Options

Dual-redundant (1+1) AC and DC power options:

- 1600 W 48 VDC per PSU
- 800 W 28 VDC per PSU
- 1600 W 120 VAC per PSU
- 240 VAC per PSU
- MIL-461 options: 2x MIL-STD 750 W 120 VAC, 28 VDC 500 W

#### Environmental\*

##### Operating


Temperature: 0°C to 50°C, configuration dependent

Humidity: 5% - 95%, non-condensing

Shock: 3 axis, 35 g, 25 ms

Vibration: 4.7 Grms vertical, 4.5 Grms longitudinal, 5 Hz to 2000 Hz

Partnering with



**Non-Operating**

Temperature: -40°C to 70°C, configuration dependent

Humidity: 5% to 95%, non-condensing

**Additional Options**

Shock pins

Slide rails

Cable accessories

**Mechanical**

Height: 2U or 3.5" (88.9 mm)

Width: 17.36" (440.9 mm)


Depth: 22" (558.8 mm) from front to back, 21" (533.4 mm) from ear to back

Weight (Typical)\*: 37 lb

19" rackmountable

\*Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.

**Product Naming Chart**



Front View



Rear View



**Corporate Headquarters**

50 Minuteman Road  
Andover, MA 01810 USA  
+1 978.967.1401 tel  
+1 866.627.6951 tel  
+1 978.256.3599 fax

**International Headquarters**

**Mercury International**

Avenue Eugène-Lance, 38  
PO Box 584  
CH-1212 Grand-Lancy 1  
Geneva, Switzerland  
+41 22 884 51 00 tel

**Learn more**

Visit: [mrcy.com/servers](http://mrcy.com/servers)

Contact: [servers@mrcy.com](mailto:servers@mrcy.com)



The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, and BuiltSECURE. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

