

SCFE6931

Configurable, low-latency, OpenVPX™ heterogeneous processing module

AI core board for faster and more efficient processing

- Dual Xilinx Versal® AI Core ACAP processors
- OpenVPX™ compliant for ease of integration
- Supports multiple high-reliability cooling options
- Fiber optic interfaces to maximize bandwidth



Mercury's SCFE6931 is a versatile OpenVPX heterogeneous processing module designed for high performance and agile system integration. Incorporating Xilinx's Versal® ACAP (Adaptive Compute Acceleration Platform) processors and advanced networking architecture, this advanced module maximizes application performance by combining scalar processing, vector processing and programmable logic into a single 6U design.

Built-in mid-board fiber transceivers enable maximum customization and support high-speed digitization cards. Designed to be delivered in multiple cooling options, the SCFE6931 is ideal for applications that require high-performance operation in harsh environments.

SPECIFICATIONS

Physical

- Single-slot 6U OpenVPX form factor
- OpenVPX interface compliant with ANSI/VITA 65-2010 (R2013)
- Optical mid-board
- Up to 16 Rx/Tx mid-board fiber transceivers per Versal AI Core ACAP

Backplane Interface

- VITA 65 slot profile SLT6-PAY-4F1Q2U2T-10.2.1
- VITA 66.x capable on P3 and P6
- Two Xilinx Versal AI Core VC1902 ACAPs

Memory

- 48 GB of DDR4 SDRAM (24 GB per ACAP)

Other

- Vita 46.11 IPMI controller
- Sensor interface to monitor temperature, voltage
- Power sequencing
- Secure JTAG
- Manufactured in an AS9100D facility

HIGH DATA RATE OPTICAL INTERFACE

Currently implemented at 25 Gbps, the SCFE6931 has integrated mid-board fiber transceivers for connectivity to external system components via VITA 66.x.

ADVANCED FPGA FUNCTIONALITY

Mercury’s processing modules leverage our EchoCore® FPGA IP that allows customers to focus on their application while building on the groundwork to provide basic infrastructure functionality right out of the box. Mercury facilitates the re-use of common IP across FPGAs to optimize time-to-market and reduce development time. Mercury simplifies application integration by providing a standard control plane interface using AXI4-Lite connectivity and uses AXI4-Stream switches for routing data within the FPGA and to external interfaces, such as PCIe. Customers can use their design tool of choice, such as parameterizable Xilinx IPs, HLS or RTL to generate signal processing algorithms. The cores are then instantiated into a reserved user block and compiled into the FPGAs.

ENVIRONMENTAL

VITA - Standard Product Environmental Qualification Levels

	RUGGED LEVEL	AIR FLOW-BY
Temperature	Operating	-40° C to +71° C (at module edge)
	Storage	-55° C to +125° C
	Max Rate of Change	10° C/min
Humidity	Operating*	5-95%, non-condensing
	Storage	100% condensing
Altitude	Operating*	0-70,000 ft
	Storage	0-70,000 ft
Vibration	Random	0.1 g2/Hz; 5-2000 Hz, 1 hr/axis
	Sine	10G peak; 5-2000 Hz, 1 hr/axis
	Shock	z-axis: 50g; x and y-axes: 80g; (11ms, 1/2-sine pulse, 3 positive, 3 negative)
Salt/Fog		10% NaCl
VITA 47		Contact Factory

* Customer must maintain required cfm level. Consult factory for the required flow rates.

Storage Temperature is defined per MIL-STD-810F, Method 502.4, para 4.5.2, where the product under non-operational test is brought to an initial high temperature cycle to remove moisture. Then the unit under non-operational test will be brought to the low storage temperature. The low temperature test is maintained for 2 hours. The product is then brought to the high storage temperature and is maintained for 2 hours. The product is then brought back to ambient temperature. All temperature transitions are at a maximum rate of 10° C/min. One cold/hot cycle constitutes the complete non-operational storage temperature test. This assumes that the board level products are individually packaged in accordance with ASTM-D-3951 approved storage containers. These tests are not performed in Mercury shipping containers, but in an unrestrained condition. Please consult the factory if you would like additional test details.


All products manufactured by Mercury meet elements of the following specifications: MIL-STD-454, MIL-STD-883, MIL-HDBK-217F, and MIL-I-46058 or IPC-CC-830, and various IPC standards. Mercury’s inspection system has been certified in accordance with MIL-I-45208A.

PORTABILITY

Multiple generations of this product family provide the signal processing functionality that enables systems to nimbly respond to emerging threats. Examples include:

- Wideband search using full sample-rate FFTs and threshold-detection processing
- Channelizers and multiple independent/coherent digital down/up converter channels with integrated filtering, gain balancing, high-precision receive-time tagging and transmit scheduling, VITA
- 49.x signal data and context packet generation and reception/depacketizing
- Non-coherent and low-latency coherent EA technique generation
- Communications modem functions
- Instantaneous bandwidths (IBW) in excess of 1 GHz have been implemented and transferred, as well as multiple simultaneous down-converted signal streams of over 100 MHz IBW.

SCFE6931 SLOT PROFILE



Corporate Headquarters

50 Minuteman Road
 Andover, MA 01810 USA
 +1 978.967.1401 tel
 +1 866.627.6951 tel
 +1 978.256.3599 fax

International Headquarters

Mercury International
 Avenue Eugène-Lance, 38
 PO Box 584
 CH-1212 Grand-Lancy 1
 Geneva, Switzerland
 +41 22 884 51 00 tel

Learn more

Visit: mrcy.com/scfe6931



The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, and BuiltSECURE. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

