


# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Description


AM6031 is a Single-Pole Double-Throw (SPDT) absorptive switch covering the DC to 20 GHz frequency range. The positive control device exhibits high isolation and low insertion loss over the operating temperature range of -40C to +85C.





## Features

- 1.5 dB Insertion Loss
- +45 dBm Input IP3
- +3.3V to +5.0V Supply
- +3.3V to +5.0V Control
- >43 dB Isolation
- 3mm QFN
- -40C to +85C Operation

## Functional Diagram



## Characteristic Performance



# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Table of Contents

Description .....	1	DC Electrical Characteristics .....	5
Features .....	1	RF Performance .....	5
Functional Diagram .....	1	Timing Characteristics .....	5
Characteristic Performance .....	1	State Table .....	5
Revision History .....	2	Typical Performance .....	6
Pin Layout and Definitions .....	3	Typical Application .....	8
Specifications .....	4	3mm 16 Lead QFN Details .....	9
Absolute Maximum Ratings .....	4	Evaluation PC Board .....	10
Handling Information .....	4	Related Parts .....	10
Recommended Operating Conditions .....	4	Component Compliance Information .....	11


## Revision History

Date	Revision Number	Notes
October 23, 2019	1	Initial Release
November 8, 2019	2	Pinout Corrected
February 12, 2020	3	Pinout Updated. Information about extending bandwidth to below 400 MHz added.

# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Pin Layout and Definitions



Pin Number	Pin Name	Pin Function
1-2	GND	Ground – Common
3	RFC	RFC Input – 50 Ohms – DC Coupled. External DC blocking capacitor required*
4-6	GND	Ground – Common
7	RF2	RF2 Output – 50 Ohms – DC Coupled. External DC blocking capacitor required*
8	GND	Ground – Common
9	ACG	Optional AC Ground**
10	VDD	DC Power Input
11	CTL	Switch Control
12	ACG	Optional AC Ground**
13	GND	Ground – Common
14	RF1	RF1 Output – 50 Ohms – DC Coupled. External DC blocking capacitor required*
15-16	GND	Ground – Common

**Notes:**

- \* DC Blocking caps not required if in series with other Atlanta Micro parts of the same reference voltage
- \*\* AC Ground caps optional. Installing AC ground capacitors offer optimum absorptive performance below 400 MHz. See *Typical Performance* section for more details.

# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Specifications

### Absolute Maximum Ratings

	Minimum	Maximum
Supply Voltage	-0.3 V	+6.0 V
RF Input Power		+27 dBm
Operating Junction Temperature	-40 C	+150 C
Storage Temperature Range	-50 C	+150 C

**Note:** Any device operation beyond the Absolute Maximum Ratings may result in permanent damage to the device. The values listed in this table are extremes and do not imply functional operation of the device at these or any other conditions beyond what is listed under Recommended Operating Conditions. Any part subjected to conditions outside of what is recommended for an extended amount of time may suffer from reliability concerns.

### Handling Information

	Minimum	Maximum
Storage Temperature Range (Recommended)	-50 C	+125 C
Moisture Sensitivity Level	MSL 3	



Atlanta Micro products are electrostatic sensitive.  
Follow safe handling practices to avoid damage

### Recommended Operating Conditions

	Minimum	Typical	Maximum
Supply Voltage	+2.5 V	+5.0 V	
Operating Case Temperature	-40 C		+85 C
Operating Junction Temperature	-40 C		+125 C

# AM6031 – Switch

## DC to 20 GHz SPDT, Absorptive

### DC Electrical Characteristics

(T = 25 °C unless otherwise specified)

Parameter	Testing Conditions	Minimum	Typical	Maximum
DC Supply Voltage		+2.5 V	+5.0 V	
DC Supply Current	VDD = +3.3 V		1 mA	
	VDD = +5.0 V		1 mA	
Power Dissipated	VDD = +3.3 V		3.3 mW	
	VDD = +5.0 V		3.3 mW	
Logic Level Low		0.0 V		+0.5 V
Logic Level High		+2.0 V		+VDD

### RF Performance

(T = 25 °C unless otherwise specified)

Parameter	Testing Conditions	Minimum	Typical	Maximum
Frequency Range		DC		20 GHz
Insertion Loss	f = 0.01 GHz		1 dB	
	f = 10 GHz		1.5 dB	
	f = 20 GHz		2.5 dB	
Return Loss	f = 0.01 GHz		30 dB	
	f = 10 GHz		17 dB	
	f = 20 GHz		20 dB	
Input IP3	VDD = +5.0V		+45 dBm	
Isolation	VDD = +5.0V		+43 dBm	

### Timing Characteristics

Parameter	Minimum	Typical	Maximum
Switching Speed (Path Enabled to Disabled)		10 ns	
Switching Speed (Path Disabled to Enabled)		30 ns	

### State Table




CTL	State
Low	RFC to RF1
High	RFC to RF2

# AM6031 – Switch

## DC to 20 GHz SPDT, Absorptive

### Typical Performance

(VDD = +5.0 V. Data measured via probes outside IC package on 10 mil Rogers RO4350B™)







Notes: \*measurements made with Configuration A. See *Typical Application* for more information.

# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Typical Performance (continued)

(VDD = +5.0 V, T = 25 C. Data measured on 10 mil Rogers RO4350B™)




# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Typical Applications

Configuration A: 400 MHz to 20 GHz



### Recommended Component List (or equivalent):

Part	Value	Part Number	Manufacturer
C1-C3	0.1 $\mu$ F	0201BB104KW160	Passives Plus
C4	0.1 $\mu$ F	C1005X7R1H104K050BB	TDK
FB1	-	MMZ1005A222E	TDK

### Notes:

1. DC blocking capacitors should be high performance, low-loss, broadband capacitors for optimal performance.
2. RC Filtering on the control line is recommended to prevent digital noise from coupling to the RF path.
  - a. Select control line RC filter values based on desired logic source decoupling and switching speed.




# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Typical Applications (continued)

Configuration B: DC to 20 GHz



### Recommended Component List (or equivalent):

Part	Value	Part Number	Manufacturer
C1-C3	0.1 $\mu$ F	0201BB104KW160	Passives Plus
C4-C6	0.1 $\mu$ F	C1005X7R1H104K050BB	TDK
FB1	-	MMZ1005A222E	TDK


### Notes:

1. DC blocking capacitors should be high performance, low-loss, broadband capacitors for optimal performance.
2. RC Filtering on the control line is recommended to prevent digital noise from coupling to the RF path.
  - a. Select control line RC filter values based on desired logic source decoupling and switching speed.

# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

Evaluation PC Board



## Related Parts

Part Number	Description		
AM6012	DC	to 18 GHz	SPDT, Reflective
AM6013	DC	to 18 GHz	SP4T, Reflective
AM6015	DC	to 18 GHz	SP6T, Reflective
AM6016	DC	to 26.5 GHz	SPDT, Reflective
AM6029	DC	to 18 GHz	SP4T, Reflective

# AM6031 – Switch

DC to 20 GHz SPDT, Absorptive

## Component Compliance Information

**RoHS:** Atlanta Micro, Inc. hereby certifies that all products comply with the EC Directive 2011/65/EC on the Restriction of Hazardous Substances, commonly known as EU-RoHS 6 and 10. All products supplied by Atlanta Micro shall be compliant with the European Directive 2011/65/EC based on the following substance list.

Substance List	Allowable Maximum Concentration
Lead (Pb)	<1000 PPM (0.1% by weight)
Mercury (Hg)	<1000 PPM (0.1% by weight)
Cadmium (Cd)	<75 PPM (0.0075% by weight)
Hexavalent Chromium (CrVI)	<1000 PPM (0.1% by weight)
Polybrominated Biphenyls (PBB)	<1000 PPM (0.1% by weight)
Polybrominated Diphenyl ethers (PBDE)	<1000 PPM (0.1% by weight)
Decabromodiphenyl Deca BDE	<1000 PPM (0.1% by weight)
Bis (2-ethylhexyl) Phthalate (DEHP)	<1000 PPM (0.1% by weight)
Butyl Benzyl Phthalate (BBP)	<1000 PPM (0.1% by weight)
Dibutyl Phthalate (DBP)	<1000 PPM (0.1% by weight)
Diisobutyl Phthalate (DIBP)	<1000 PPM (0.1% by weight)

**REACH:** Atlanta Micro, Inc. neither uses nor intentionally adds any of the substances considered to be a Substance of Very High Concern (SVHC) as defined by the EU Regulation (EC) No. 1907-2006 on Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH).

**Conflict Materials:** Atlanta Micro does not knowingly use materials that are sourced from the Democratic Republic of Congo (DRC) or any other known conflict regions. Atlanta Micro's supply chain is comprised of sources that are both environmentally and socially responsible. We periodically review this requirement with our vendors to ensure continued compliance.

Atlanta Micro takes its responsibility as a global partner seriously and will use due diligence within our supply chain to ensure all standards are met to the best of our knowledge.