



AVM4108C

10" Widescreen HD Multi-Function Display


Take your system interoperability even further with an HD display with line select keys

- 10.1" HD widescreen color display
- HD and SD I/O
- Sunlight-readable LCD
- Built-in heater
- Multiple screen modes
- Optional touchscreen and NVIS compatibility



Sunlight-readable and sized right


- 10.1" 16:10 aspect ratio display
- 1280 x 800 resolution
- HD and SD inputs
- Multiple screen modes
- Rugged, milled aluminum frame
- Built-in heater
- Works with mapping systems, digital video recorders and other avionics systems
- Optional variants: touchscreen, NVIS compatibility



CONTACT US



The AVM4108C offers four screen modes*: full screen, split screen (SS), picture-in-picture (PIP) and picture-by-picture (PBP), also known as side-by-side. Full-screen mode displays only one input signal and maintains the aspect ratio of the input source.



Split-screen mode displays two input signals simultaneously; these images are positioned next to each other and stretched vertically to fit the screen.



Picture-in-picture mode also displays two inputs simultaneously, one in a large format and one in a smaller window whose position is configurable via the display setup menus.



Like split screen, picture-by-picture or side-by-side mode displays two inputs next to each other; these images, however, retain the aspect ratios of their respective video inputs. Excess screen space appears as black bars.

*Modes are subject to change without notice.

SPECIFICATIONS

Dimensions

Display Area	10.1" (256.54 mm) diagonal
Height	7.09" (180.086 mm)
Width	9.84" (249.936 mm)
Depth	1.89" (48.006 mm)
Weight	5 lb (2.26 kg)

I/O

Power	28 VDC
Composite Video	1 RS-170, 1 RGB input
HD Video	2 inputs/1 output
Touchscreen	1 RS-232 interface
Signals	NTSC; PAL; STANAG3350B (RGsB); SMPTE292M

Characteristics

Max Power Draw	3.82A @ 28 VDC (w/heater)
Aspect Ratio	16:10
Resolution	1280 x 800 (WXGA)
Horizontal Viewing	160°
Vertical Viewing	160°
Contrast Ratio	800:1
Refresh Rate	60 Hz
NVIS	Class B
Operating Temperature	-40°C to +55°C
Storage Temperature	-55°C to +85°C
Cooling	Passive

Qualifications

DO-160G

Contact

mission@rcy.com
+1 850.470.8464 tel

Learn more

rcy.com/displays



© 2022 Mercury Systems, Inc. The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters, and BuiltSECURE. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.
8140.00E-0422-ds-GulfBreeze-AVM_4108C