HDslim Rugged Chassis



20.7" Deep, Rear I/O Rugged Blade Chassis

- 4 slots for 'plug and pull' blades
- Redundant AC/DC power for high availability
- Fits in commercial airline bins
- One-man lift for operations on the move
- Mobile carry case option
- MIL-STD 810G



Technical Specifications

Reliability

Safety: EN60950

RFI/EMI: EN 55032, EN 55024, EN 61000

MIL-STD 810G

Environmental*

Operating

Temperature: 0°C to 50°C

Humidity: 8% to 95% (non-condensing)

Shock: 3 axis, 35g, 25ms

Vibration: 4.76Grms, 10Hz to 2000 Hz (SSD)

Non-Operating

Temperature: -40°C to 70°C

Humidity: 5% to 95% (non-condensing)

Power Supply Options

Single or Redundant 100/240V VAC (1200W, 50/60Hz, 400Hz)

Single or Redundant 10-36 VDC, 32 Amps Single or Redundant 36-72 VDC, 18 Amps

Additional Options

Shock Pins

Front Door Filter

Slide Rails

Mechanical

Height: 4U or 7 inches (177.8mm)

Width: 9.9 inches (25.1.5mm)

Depth: 20.7 inches (526mm)

Weight: ~18.1lbs (8.21lbs)

* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight, and thermal profiles are configuration dependent. Contact Mercury for information-specific to your desired configuration requirements.

Accessories


Rugged Carry Case

Height: 10 inches, Length: 22 inches, Width: 14 inches

Material: Aluminum

Features: Detachable front/rear lids and handles

Four Chassis Slots with Redundant Power




Configure Your Way

Compute-Optimized




Mixed




Custom Expertise

For tailor-made systems with specific security and environmental requirements, email servers@mrcy.com


Front View



Side View



Top View



Innovation That Matters, and Mercury Systems are trademarks of Mercury Systems, Inc. Other product and company names mentioned may be trademarks and/or registered trademarks of their respective holders. Mercury Systems, Inc. believes this information is accurate as of its publication date and is notresponsible for any inadvertent errors. The information contained herein is subject to change without notice.

Copyright © 2020 Mercury Systems, Inc.

6580.00E-0620-DS-HDslimChassis



INNOVATION THAT MATTERS®

MERCURY SYSTEMS

50 Minuteman Road • Andover, MA 01810 USA (978) 967-1401 • Fax (978) 967-3330

MERCURY SYSTEMS INTERNATIONAL

Regus Center, 26 Avenue Jean Kuntzmann Montbonnot • 38330 France +33 608 419949