

RES AI XR6 1U

20" deep, 2 drive, rear I/O rugged High Performance Computing (HPC) rack mountable server

- Up to one NVIDIA® Tesla® GPGPUs or Quadro® GPU
- One Intel® Xeon® Scalable processor
- Up to 384GB DDR4 ECC memory
- Up to 60TB of storage and 3 PCIe 3.0 cards
- MIL-STD: 810G



Engineered to handle massive workloads anywhere, Mercury's *EnterpriseSeries™* RES AI 1U server employs the latest NVIDIA® Tesla® GPUs and Intel® Xeon® Scalable processors to accelerate compute-heavy mission-critical applications such as Signal Intelligence (SIGINT), cryptography, deep learning, Artificial Intelligence (AI), surveillance, sensor fusion, visualization, image processing, tracking and big data analytics.

Tackle Challenging Workloads at the Edge

Powered by the latest NVIDIA Volta, Pascal™ and Turing™ architecture GPUs, the RES AI 1U harnesses parallel processing to maximize throughput, boost productivity and push the boundaries of compute-heavy applications at the edge. To optimize performance in a small footprint, it densely packs multiple expansion slots, one Intel® Xeon® Scalable processor, 384GB DDR4 ECC memory and two disk drives in a 21lb, 20" deep rugged form-factor.

Fully Configurable to Your HPC Application

Equipped with numerous PCIe 3.0 slots that accommodate a mix of GPUs, FPGA accelerators and other expansion cards, RES AI accelerates an array of High Performance Computing (HPC) workloads by tailoring to unique performance, speed and storage requirements.

Supercomputing Designed for the Field

Built from the ground up to provide edge computing capability previously reserved for the datacenter, field-deployable RES AI servers incorporate innovative patented technologies and design features to withstand shock, vibration, dust, sand, and temperature extremes. To ensure uptime, availability and sustained optimal performance in almost any environment, servers feature **dual redundant, hot swappable AC or DC power supplies** and are certified to multiple military (MIL-STD) and commercial (IEC) environmental specifications. Compatible with multiple operating systems, applications and software, RES AI scales supercomputing from the Cloud to the Edge.

Proven Performance from a Trusted Partner

Mercury's EnterpriseSeries RES Servers are trusted worldwide for their high-performance, **long life cycles**, thermal resiliency, compatibility with industry standards, and **SWaP optimization**. With over 30 years of technical expertise, Mercury Systems works closely with customers to design computing solutions that are easy to integrate, affordable and reliable for years to come.

Mercury Systems is a leading commercial provider of secure sensor and safety-critical processing subsystems. Optimized for customer and mission success, Mercury's solutions power a wide variety of critical defense and intelligence programs.



Modified COTS Expertise

For customized space, environmental, and performance requirements email tms@mrchy.com

Technical Specifications

1 Intel® Xeon® Scalable CPUs with up to 26 cores per processor
Up to 1 double-wide NVIDIA Tesla or Quadro GPU accelerator
Up to 384GB memory with 6 DIMM slots, 2933MHz RDIMM/LRDIMM

Management and Operating System

Windows®, Linux®, VMWARE® and other hypervisors
IPMI v2.0, Redfish option available
TPM 1.2 or 2.0 support

Expansion and Modular Maintainability

2 Disk on Module (up to 128GB per DOM)
2 USB 3.0 (internal)
2 2280 M.2 (PCIe x4 or SATA3)
3 PCIe 3.0 card options:
(1) PCIe 3.0 x16 GPU slot + (2) PCIe 3.0 x16

Input/Output Versatility

Front Access

2 removable, hot pluggable, 2.5" SATA/SAS3 drives, U.2 NVME option available
1 power switch

Rear Access

2 10GBaseT Ethernet Ports (RJ45)
2 USB 3.0
4 USB 2.0
1 IPMI 2.0
1 VGA graphic Port

Power Supply Options

Single or Redundant 100/240 VAC, 47/63/400Hz, 600W
Single or Redundant 48 VDC, 600W

Environmental*

Operating

Temperature: 0°C to 50°C
Extended temperature: -15°C to 65°C
Humidity: 8% to 95% (non-condensing)
Shock: 3 axis, 35g, 25ms
Vibration: 4.76Grms, 10Hz to 2000 Hz (SSD)

Non-Operating

Temperature: -40°C to 70°C
Humidity: 5% to 95% (non-condensing)

Additional Options

Shock pins
Front door filter
Slide rails

Mechanical

Height: 1U or 1.75" inches (44.45mm)
Width: 17 inches (433.3mm)
Depth: 20 inches (508mm)
Weight (Typical)*: 21 pounds (9.5kg)
19" rackmountable

* Mercury Systems designs all products to meet or exceed listed data sheet specifications. Some specifications including I/O profiles, weight, and thermal profiles are configuration dependent. Contact Mercury for information specific to your desired configuration requirements.



The Mercury Systems logo and the following are trademarks or registered trademarks of Mercury Systems, Inc.: Mercury Systems, Innovation That Matters. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury believes this information is accurate as of its publication date and is not responsible for any inadvertent errors. The information contained herein is subject to change without notice.

Copyright © 2019 Mercury Systems, Inc.

6562.00E-0419-DS-RESA1U2dr

EXPID14681



INNOVATION THAT MATTERS™

MERCURY SYSTEMS

47200 Bayside Parkway • Fremont, CA 94538 USA
(510) 252-0870 • Fax (510) 490-5529

MERCURY SYSTEMS INTERNATIONAL

26 Avenue Jean Kuntzmann
Monbonnot-Saint-Martin • 38330 France
+33 608 419949