


AM3275 – Filter Bank

6 GHz to 18 GHz Bandpass Filter Bank




The AM3275 is a bandpass filter bank covering 6 GHz to 18 GHz in 4 tunable bands of at least 2 GHz bandwidth each. The bank features four separate tunable filter bands each with four states. With internal 50Ω matching in a 5mm QFN, the AM3275 represents a low loss filter solution for SWaP-constrained applications.


FEATURES

- Covers 6 to 18 GHz in 4 tunable bands
- 6 dB Typical Insertion Loss
- Additional 10 GHz bypass path for low frequency extension
- +3.3V to +5.0V Supply
- +3.3V to +5.0V Control
- 5mm QFN Package
- -40°C to +85°C Operation

FUNCTIONAL DIAGRAM



CHARACTERISTIC PERFORMANCE





CONTENTS

FEATURES 1

FUNCTIONAL DIAGRAM 1

CHARACTERISTIC PERFORMANCE 1

REVISION HISTORY..... 2

PIN LAYOUT AND DEFINITIONS 3

SPECIFICATIONS..... 4

TYPICAL PERFORMANCE 7

TYPICAL PERFORMANCE (CONTINUED)..... 8

TYPICAL APPLICATION.....12

EVALUATION PC BOARD.....13


RELATED PARTS.....13

COMPONENT COMPLIANCE INFORMATION14

REVISION HISTORY

Date	Revision	Notes
July 16, 2025	1	Initial Release

PIN LAYOUT AND DEFINITIONS



Pin	Name	Function
1	GND	Ground – Common
2	AUX1	Filter Bypass Input Side – 50 Ohms – DC Coupled, External DC Blocking Cap Required
3	GND	Ground – Common
4	RF IN	RF Input – 50 Ohms – DC Coupled, External DC Blocking Cap Required
5	GND	Ground – Common
6,7	NC	No Connect
8	VDD	DC Power Input
9	NC	No Connect
10	VB	Bypass Switch Control
11,12	NC	No Connect
13	V0	Switch Control D
14	V1	Switch Control C
15	V2	Switch Control B
16	V3	Switch Control A
17-19	NC	No Connect

Pin	Name	Function
20	GND	Ground – Common
21	RF OUT	RF Output – 50 Ohms – DC Coupled, External DC Blocking Cap Required
22	GND	Ground – Common
23	AUX2	Filter Bypass Output Side – 50 Ohms – DC Coupled, External DC Blocking Cap Required
24	GND	Ground – Common
25-32	NC	No Connect
Note: NC pins may be grounded or left open		

SPECIFICATIONS

Absolute Maximum Ratings

	Minimum	Maximum
RF Input Power		+27 dBm
Operating Junction Temperature	-40 C	+150 C
Storage Temperature Range	-55 C	+150 C

Note: Any device operation beyond the Absolute Maximum Ratings may result in permanent damage to the device. The values listed in this table are extremes and do not imply functional operation of the device at these or any other conditions beyond what is listed under Recommended Operating Conditions. Any part subjected to conditions outside of what is recommended for an extended amount of time may suffer from reliability concerns.

Handling Information

	Minimum	Maximum
Moisture Sensitivity Level	MSL 3	
ESD classification (HBM survivable)	Class 0A	



Mercury products are electrostatic sensitive.
Follow safe handling practices to avoid damage.

Recommended Operating Conditions

	Minimum	Typical	Maximum
Supply Voltage		+3.3 V	+5.0 V
Operating Case Temperature	-40 C		+85 C

Thermal information

	Thermal Resistance (°C / W)
Junction to Case Thermal Resistance (θJC)	80 C/W
Nominal Junction Temperature at +85C ambient	92 C
Channel Temperature to Maintain 1 Million Hour MTTF	105 C

Timing Characteristics

Parameter	Minimum	Typical	Maximum
Band Switching Speed		24 ns	
Intra-band Tuning Speed		100 ns	

Note: Measured as configured in typical application. Trigger points are 50% control and 90% RF.

DC Electrical Characteristics

(T = 25 °C unless otherwise specified)

Param	Testing Conditions	Min	Typical	Max
DC Supply Voltage		+3.0 V	+3.3 V	+5.2 V
DC Supply Current	VDD = +3.3V		7 mA	
	VDD = +5.0V		7 mA	
Power Dissipated	VDD = +3.3V		23.1 mW	
	VDD = +5.0V		35 mW	
Logic Level Low		-0.1 V		+0.5 V
Logic Level High		+2.0 V		+VDD V

Param	Testing Conditions	Min	Typical	Max
Frequency Range				
	Bypass (Aux)	-		16 GHz
	Band 1	5.5 GHz		11.5 GHz
	Band 2	9 GHz		14.5 GHz
	Band 3	11.5 GHz		16.5 GHz
	Band 4	13.5 GHz		18 GHz

RF Performance

(T = 25 °C unless otherwise specified)





Param	Testing Conditions	Min	Typical	Max
Insertion Loss	VDD = +3.3V			
	Band 1		5 dB	
	Band 2		6 dB	
	Band 3		6 dB	
	Band 4		7 dB	
	Bypass (Aux)		1.5 dB	
Return Loss	VDD = +3.3V		-15 dB	

State Table

V3	V2	V1	V0	VB	Filter Band
L	L	L	L	L	Band 1(5.5 GHz – 11.5 GHz) State 00
H	L	L	L	L	Band 1(5.5 GHz – 11.5 GHz) State 01
L	H	L	L	L	Band 1(5.5 GHz – 11.5 GHz) State 10
H	H	L	L	L	Band 1(5.5 GHz – 11.5 GHz) State 11
L	L	H	L	L	Band 2(9 GHz – 14.5 GHz) State 00
H	L	H	L	L	Band 2(9 GHz – 14.5 GHz) State 01
L	H	H	L	L	Band 2(9 GHz – 14.5 GHz) State 10
H	H	H	L	L	Band 2(9 GHz – 14.5 GHz) State 11
L	L	H	H	L	Band 3(11.5 GHz – 16.5 GHz) State 00
H	L	H	H	L	Band 3(11.5 GHz – 16.5 GHz) State 01
L	H	H	H	L	Band 3(11.5 GHz – 16.5 GHz) State 10
H	H	H	H	L	Band 3(11.5 GHz – 16.5 GHz) State 11
L	L	L	H	L	Band 4(13.5 GHz – 18 GHz) State 00
H	L	L	H	L	Band 4(13.5 GHz – 18 GHz) State 01
L	H	L	H	L	Band 4(13.5 GHz – 18 GHz) State 10
H	H	L	H	L	Band 4(13.5 GHz – 18 GHz) State 11
X	X	X	X	H	Bypass (Aux) path






TYPICAL PERFORMANCE

(T = 25 °C and VDD = +3.3V unless otherwise specified.)








TYPICAL PERFORMANCE (CONTINUED)

(T = 25 °C and VDD = +3.3V unless otherwise specified.)








TYPICAL PERFORMANCE (CONTINUED)

(T = 25 °C and VDD = +3.3V unless otherwise specified.)








TYPICAL PERFORMANCE (CONTINUED)

(T = 25 °C and VDD = +3.3V unless otherwise specified.)




TYPICAL PERFORMANCE (CONTINUED)

(T = 25 °C and VDD = +3.3V unless otherwise specified.)



The measured data shown here does not include pcb, connectors, and blocking capacitors

TYPICAL APPLICATION




Recommended Component List (or Equivalent)

Part	Value	Part Number	Manufacturer
C1-C4	0.1 μ F	0201BB104KW160	Passives Plus
FB1		MMZ1005A222E	TDK

Notes:

1. DC blocking capacitors should be low-loss, broadband capacitors for optimum performance.
2. Control lines are filtered internally to provide isolation. External R-C filtering may be added to increase isolation at the expense of switching speed.

EVALUATION PC BOARD



RELATED PARTS

Part Number		Description
AM3153	6 GHz to 26.5 GHz	Digitally Tunable Bandpass Filter Bank
AM3186	6 GHz to 26.5 GHz	Sub-Octave Bandpass Filter Bank
AM3194	6 GHz to 18 GHz	Sub-Octave Bandpass Filter Bank
AM3163	2 GHz to 18 GHz	Digitally Tunable Bandpass Filter Bank

COMPONENT COMPLIANCE INFORMATION

RoHS: Mercury Systems, Inc. hereby certifies that all products comply with the EC Directive 2011/65/EC on the Restriction of Hazardous Substances, commonly known as EU-RoHS 6 and 10. All products supplied by Mercury shall be compliant with the European Directive 2011/65/EC based on the following substance list.

Substance List	Allowable Maximum Concentration
Lead (Pb)	<1000 PPM (0.1% by weight)
Mercury (Hg)	<1000 PPM (0.1% by weight)
Cadmium (Cd)	<75 PPM (0.0075% by weight)
Hexavalent Chromium (CrVI)	<1000 PPM (0.1% by weight)
Polybrominated Biphenyls (PBB)	<1000 PPM (0.1% by weight)
Polybrominated Diphenyl ethers (PBDE)	<1000 PPM (0.1% by weight)
Decabromodiphenyl Deca BDE	<1000 PPM (0.1% by weight)
Bis (2-ethylhexyl) Phthalate (DEHP)	<1000 PPM (0.1% by weight)
Butyl Benzyl Phthalate (BBP)	<1000 PPM (0.1% by weight)
Dibutyl Phthalate (DBP)	<1000 PPM (0.1% by weight)
Diisobutyl Phthalate (DIBP)	<1000 PPM (0.1% by weight)

REACH: Mercury Systems, Inc. neither uses nor intentionally adds any of the substances considered to be a Substance of Very High Concern (SVHC) as defined by the EU Regulation (EC) No. 1907-2006 on Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH).

Conflict Materials: Mercury does not knowingly use materials that are sourced from the Democratic Republic of Congo (DRC) or any other known conflict regions. Mercury's supply chain is comprised of sources that are both environmentally and socially responsible. We periodically review this requirement with our vendors to ensure continued compliance.

Mercury takes its responsibility as a global partner seriously and will use due diligence within our supply chain to ensure all standards are met to the best of our knowledge.



Corporate Headquarters

50 Minuteman Road
Andover, MA 01810 USA
+1 978.967.1401 tel
+1 866.627.6951 tel
+1 978.256.3599 fax

International Headquarters

Mercury International

Avenue Eugène-Lance, 38
PO Box 584
CH-1212 Grand-Lancy 1
Geneva, Switzerland
+41 22 884 5100 tel

Learn more

Visit: mrcy.com

For pricing details, contact: MMICsales@mrcy.com

For technical details, contact: MMICsupport@mrcy.com



The Mercury Systems logo is a registered trademark of Mercury Systems, Inc. Other marks used herein may be trademarks or registered trademarks of their respective holders. Mercury products identified in this document conform with the specifications and standards described herein. Conformance to any such standards is based solely on Mercury's internal processes and methods. The information contained in this document is subject to change at any time without notice.

