

Diplexer C5938



Specifications are subject to change without notice

Electrical Specifications (+25°C)

Parameter	Value	
	Channel 1	Channel 2
Passband	2500 to 4000 MHz	4000 to 7500 MHz
Insertion Loss	1.0 dB Typical	1.0 dB Typical
VSWR	1.5:1 Maximum	1.5:1 Maximum
Isolation	20 dB Typical	20 dB Typical
Rejection	30 dB at 1600 MHz 45 dB at 7000 MHz	40 dB at 2400 MHz 80 dB at 1600 MHz
Power Handling	50 Watts CW	50 Watts CW
Crossover	4.0 dB at 4000 MHz	
Connectors	N Female per MIL-C-39012	
Weight	9.1 oz., 0.57 lb.	
Package Size	1.0" x 1.5" x 2.1"	


Features

- High Power
- Low Loss

Applications

- Wireless
- Test Equipment

Outline Drawing



All dimensions are in inches

Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at rf.microwave@rcy.com or visit www.rcy.com/rf for a detailed listing of RF and Microwave products.



Corporate Headquarters • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • www.rcy.com