

Low Noise Amplifier

DM-LNMB-13-101



Specifications are subject to change without notice

Electrical Specifications (+25°C)

Parameter	Value
Frequency	0.1 to 26.5 GHz
Small Signal Gain	13 dB min, 15 dB typ
Flatness	±2.0 dB max
Noise Figure (>500MHz)	5.5 dB max, 5 dB typ
P1dB	+15 dBm min
OIP3	+23 dBm typ
Input VSWR	2.2:1 nom
Output VSWR	2.2:1 nom
DC Power	+12 to +15 VDC, 200 mA nom
Max Input Power	+10 dBm CW

Mechanical Specifications

Parameter	Value
Size (L x W x H)	0.89" x 1.05" x 0.39"
Connectors (In/Out)	SMA female
Housing Material	Aluminum
Sealing	Hermetic
Cooling	External heatsink (not included)

Features

Internal Voltage Regulator

Environmental Specifications (by design)

Parameter	Value
Operating Temperature	-40 to +85°C
Storage Temperature	-54 to +85°C
Relative Humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 30,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at rf.microwave@rcy.com or visit www.rcy.com/rf for a detailed listing of RF and Microwave products.



Corporate Headquarters • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • www.rcy.com

6959.00E-1018-SS-DM-LNMB-13-101-amp