

Medium Power Amplifier

DM-MPMB-18-101



Specifications are subject to change without notice

Electrical Specifications (+25°C)

Parameter	Value
Frequency	2 to 18 GHz
Small Signal Gain	18 dB min
Flatness	±1.25 dB max
Noise Figure	5.6 dB max
P1dB	24 dBm min
IP3	32 dBm nom
VSWR (input/output)	2.0:1 nom
DC Power	+11 to 15+ VDC, 500 mA nom
Max Input Power	+15 dBm CW

Features

Internal Voltage Regulator
Reverse Voltage Protection

Environmental Specifications (by design)

Parameter	Value
Operating Temperature	-40 to +85°C
Storage Temperature	-54 to +85°C
Relative Humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 30,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

Mechanical Specifications

Parameter	Value
Size (L x W x H)	0.998" x 0.75" x 0.365"
Connectors (In/Out)	SMA (f)/SMA (f)
Sealing	Hermetic
Finish	Grey Paint, Mounting surface Ni finish
Marking	Black per MIL-STD-130

Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at rf.microwave@rcy.com or visit www.mrcy.com/rf for a detailed listing of RF and Microwave products.



Corporate Headquarters • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • www.mrcy.com

6965.00E-1018-SS-DM-MPMB-18-101-amp