



## FEATURES

### MECHANICAL INTEGRITY

- ▶ Rack-optimized design for unique user requirements
- ▶ Designed for high reliability in harsh operating environments
- ▶ Specially coated aluminum for light weight and corrosion resistance
- ▶ Stainless steel reinforcement for strength and stiffness
- ▶ Modular design for easy upgrade and service
- ▶ Optional rack-mount slides
- ▶ Front-to-rear airflow direction

### MANAGEMENT AND OPERATING SYSTEM

- ▶ Windows® and Linux® application support
- ▶ IPMI v2.0 support

### ENVIRONMENTAL RESILIENCY\*

- ▶ Operating shock: 3 axis, 35G, 25ms
- ▶ Operating vibration: 3.0 Grms, 8 Hz to 2000 Hz
- ▶ Operating temperature: 0°C – 55°C
- ▶ Humidity: 8% to 90% non-condensing

\* Environmental specifications are configuration dependent.

### MODULAR MAINTAINABILITY

- ▶ Power supply options
  - Single or redundant 110/220 VAC, (50/60Hz, 400Hz)
  - Single or redundant 18-36 VDC 32 Amp
  - Single or redundant 36-72 VDC 18 Amp

### MILSPEC

- ▶ MIL-STD-810G (Shock and Vibration)

## RES-32XR3 FIO

### 3U Two Socket, 13 or 17 Inch Depth Rack Mountable Server

### OVERVIEW

The Themis RES-32XR3 FIO Dual-Processor socket server, combines the robust design of the Rugged Enterprise Server (RES) family with the latest 5500 and 5600 series Intel® Xeon® processors.

Themis extensive thermal and kinetic management expertise makes these high performance systems suitable for mission-critical applications in demanding environments.

The RES-32XR3 FIO is configured with one or two Intel Xeon 5500 or 5600 Series Processors and features multiple expansion slots, extensive high-speed I/O, and multiple storage options that provide users with configuration versatility and system expansion to meet current and future system requirements.



*FIGURE 1: Themis RES-32XR3 FIO Rack Mountable Server*

## UNMATCHED FLEXIBILITY

The RES-32XR3 FIO has all I/O accessible from the front of the machine. Power supplies, disk drives, Gigabit Ethernet controllers and graphics port are also front-panel accessible. The RES-32XR3 FIO features a shallow 13 inch (318.5 mm) or a 17 inch (431.8 mm) chassis depth. Front access and shallow depth make the RES-32XR3 FIO an ideal solution for space constrained environments.

The RES-32XR3 FIO combines the robust design of the Rugged Enterprise Server (RES) family, with the latest 5500 and 5600 series Intel® Xeon® processors.

Designed for operation use in harsh operating environments, Themis RES systems incorporate advanced thermal and mechanical design features including: dual, redundant, hot swappable AC and DC power supply options.

This system combines the Intel four and six core Xeon processors, with advanced thermal and mechanical design techniques, to achieve I/O configuration flexibility and high reliability in high shock and vibration environments.

Featuring multiple expansion slots, extensive high speed I/O, and multiple storage options, the RES-32XR3 FIO allows users versatile configurability and system expansion. The addition of commercially available, off-the-shelf networking cards, graphics, I/O, peripherals, and other value-added options provides users even greater flexibility to meet current and future system requirements.

Aluminum die cast front and rear panels, and a 13- or 17-inch deep chassis constructed from strong, lightweight aluminum, improve system resistance to corrosion, and makes Themis systems attractive candidates for use in programs where Size, Weight, and Power (SWAP) are essential considerations.

## TECHNICAL SPECIFICATIONS

### Processor and Memory

PARAMETER	DESCRIPTION
Processor	One or two 5500 or 5600 Series Intel Xeon Processors
Memory	Up to 96 GB DDR3 ECC

### On-Board Expansion

PARAMETER	OPTIONS
Expansion slot (varies with configuration)	Up to 7 PCI-E slots or PCI-X and PCI available on some configurations

### Front Panel and Rear Panel Access I/O *Note 1*

I/O	QUANTITY	ACCESS
Removable 2.5" SATA or SAS Drives	Up to 3	Front panel
Optional CD-RW/DVD-RW drive	1	Front panel
Status LEDs		Front panel
Gigabit Ethernet ports (RJ45)	2 or 4	Front panel
RS-232 serial ports (DB9)	1 or 2	Front panel
VGA ports	1	Front panel
USB 2.0 ports	Up to 6 standard	Front panel
PS/2 keyboard and mouse ports		Front panel
Power connector	1 or 2	Front panel
Power switch	1	Front panel

### Environmental

PARAMETER	NON-OPERATING	OPERATING
Temperature range	-40° C – 70° C	0° C – 55° C <i>Note 2</i>
Humidity (non-condensing)	5% to 95%	8% to 90%
Shock	25G @ 12-40 ms	25G @ 12-40 ms
Vibration (10-2000Hz)	3.0 Grms, 8 Hz to 2000 Hz	3.0 Grms, 8 Hz to 2000 Hz
Safety	UL 1950, CSA 950	UL 1950, CSA 950
RFI/EMI	FCC class B <sup>1</sup>	

### Modular Maintainability

PARAMETER	DESCRIPTION
Hot swappable fans	
Power supply options	Single or redundant 110/220 VAC (50/60Hz, 400Hz) Single or redundant 18-36 VDC, 32 Amp Single or redundant 36-72 VDC, 18 Amp
Hot swappable disk drives	

### Mechanical

PARAMETER	NON-OPERATING
Dimensions	Height: 3RU or 5.25 inches (133.35 mm) Width: 17.06 inches (433.3 mm) Depth: 13 or 17 inches (330.2 or 431.8 mm)
Chassis features	Coated aluminum for light weight and corrosion resistance Stainless steel in selected areas to add strength and stiffness Modular design for easy upgrade and service Optional rack-mount slides Front to rear airflow

#### Notes

1. I/O options are configuration dependent.
2. Up to 65° C in specially configured systems.

## THE RES-XR3 SERVER FAMILY

The Themis family of XR3 Rugged Enterprise Servers (RES) feature the latest Intel® four- and six-core Xeon® processors to provide reliability and superior server performance in the most demanding environments. The Themis rugged server design keeps mission-critical applications available, improves life-cycle management, at a substantially lower total cost of ownership. When the environment is tough and your data is critical, rely on Themis to protect it and keep it available.

understands, and works closely with customers to optimize computing solutions that are easy to integrate, yet inexpensive to own and operate. Our solutions achieve the right balance between standard commercial technology and requirements for rugged environments, optimizing space, weight, and performance. For more information on Themis products, visit [www.themis.com](http://www.themis.com)

## THEMIS VALUE

Themis provides systems manufacturers and end-users with the most modern, best-of-breed computing resources available. Package and performance scale from small form factor embedded servers to bladed servers. Themis listens,



**Corporate Headquarters**  
47200 Bayside Parkway  
Fremont, CA 94538  
Tel: 510-252-0870  
Fax: 510-490-5529  
[www.themis.com](http://www.themis.com)

**European Sales Office**  
5 rue Irène Joliot-Curie  
38320 Eybens, France  
Tel: +33.476.14.77.86  
Fax: +33.476.14.77.89

**For More Information**  
Please visit [www.themis.com](http://www.themis.com)  
or contact Themis sales at  
510-252-0870.



©2012 Themis Computer. All rights reserved. Themis Computer, Themis and the Themis logo are trademarks or registered trademarks of Themis Computer. All other trademarks are the property of their respective owners. Themis reserves the right to change the specifications in this document without notice. All rights reserved. To ensure that you have the latest version of this document, visit [www.themis.com](http://www.themis.com).