

# Low Noise Amplifier

## DM-LNKA-30-101



Specifications are subject to change without notice

### Electrical Specifications (+25°C)

Parameter	Value
Frequency	24 to 30 GHz
Small Signal Gain	30 dB min
Flatness	±2.5dB max
Noise Figure	4.0 dB max
P1dB	+10 dBm min
IP3	+20 dBm nom
VSWR (input/output)	2.0:1 nom
DC Power	+12 VDC, 120 mA nom
Max Input Power	+10 dBm CW

### Environmental Specifications (by design)

Parameter	Value
Operating Temperature	-40 to +85C
Storage Temperature	-54 to +85°C
Relative Humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 30,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

### Mechanical Specifications

Parameter	Value
Size (L x W x H)	0.998" x 0.75" x 0.365"
Connectors (In/Out)	K type (female)
Housing Material	Aluminum
Sealing	Hermetic
Cooling	External heatsink (not included)

### Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at [rf.microwave@rcy.com](mailto:rf.microwave@rcy.com) or visit [www.mrcy.com/rf](http://www.mrcy.com/rf) for a detailed listing of RF and Microwave products.



Corporate Headquarters • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • [www.mrcy.com](http://www.mrcy.com)

6687.00E-0718-SS-DM-LNKA-30-101-amp