

Low Noise Amplifier

DM-LNMB-28-102



Specifications are subject to change without notice

Electrical Specifications (+25°C)

Parameter	Value
Frequency	1.0 to 12 GHz
Small Signal Gain	28 min
Flatness	±2.0 dB max
Noise Figure	2.0 dB max
P1dB	+15 dBm min
VSWR (input/output)	2.0:1 nom
DC Power	+12 to +15 VDC, 120 mA nom

Mechanical Specifications

Parameter	Value
Size (L x W x H)	1.0" x 1.75" x 0.41"
Connectors (In/Out)	SMA female
Sealing	Epoxy
Cooling	External heatsink (not included)

Features

Internal Voltage Regulator

Environmental Specifications (by design)

Parameter	Value
Operating Temperature	-20 to +70C
Storage Temperature	-55 to +85°C

Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at rf.microwave@rcy.com or visit www.mrcy.com/rf for a detailed listing of RF and Microwave products.



Corporate Headquarters • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • www.mrcy.com

6961.00E-1018-SS-DM-LNMB-28-102-amp