

# Diplexer L5972



Specifications are subject to change without notice

## Specifications (+25°C)

| Parameter          | Value                     |                           |
|--------------------|---------------------------|---------------------------|
|                    | Passband 1                | Passband 2                |
| Passband Frequency | 150 to 400 MHz            | 980 to 1600 MHz           |
| Insertion Loss     | 0.5 dB                    | 0.75 dB                   |
| VSWR               | 1.5:1                     | 1.9:1                     |
| Rejection          | 70 dB from 980 to 100 MHz | 70 dB from 150 to 400 MHz |
| Power Handling     | 100 Watts Average         | 100 Watts Average         |
| Connectors         | Type C                    |                           |
| Package Size       | 1.0" x 1.0" x 3.8"        |                           |

### Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at [rf.microwave@rcy.com](mailto:rf.microwave@rcy.com) or visit [www.rcy.com/rf](http://www.rcy.com/rf) for a detailed listing of RF and Microwave products.



**Corporate Headquarters** • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • [www.rcy.com](http://www.rcy.com)