

# 3 dB 90° Hybrid Coupler U6115



Specifications are subject to change without notice

## Electrical Specifications (+25°C)

Parameter	Value
Passband	400 to 450 MHz
Insertion Loss	0.38 dB Maximum
VSWR	1.2:1 Maximum
Isolation	20 dB Minimum
Amplitude Balance	± 0.35 dB
Rejection	60 dB from 2200 to 2290
Phase Balance	90° ± 5°
Power Handling	18 Watts
Connectors	SMA Female, SSMA Female
Weight	1.62 oz., 0.10 lb.
Package Size	0.5" x 1.5" x 2.0"

## Features

Low Loss  
Microstrip Design

## Applications

Space  
Missile  
Booster  
Test Equipment

## Need More Help? Need a Variant of This Product?

Contact Mercury's RF & Microwave engineering team at [rf.microwave@mrcy.com](mailto:rf.microwave@mrcy.com) or visit [www.mrcy.com/rf](http://www.mrcy.com/rf) for a detailed listing of RF and Microwave products.



Corporate Headquarters • 50 Minuteman Road • Andover, MA 01810 USA • (978) 967-1401 • (866) 627-6951 • Fax (978) 256-3599 • [www.mrcy.com](http://www.mrcy.com)